



FONTEMAGNA COMPACT



Cooling capacity (USG/h).....	34.05
Continuous supply (USG).....	18.16
Cold water Temperature.....	37.4°-50°F
Ice bank capacity (USG).....	4.09
Ice bank (lb).....	17.64
Cooling technology.....	ICE BANK - Double Stainless Steel coil
Condensation.....	Forced ventilation (Fan)
Adjustable Thermostat.....	Yes
Refrigerant Gas.....	Natural HYDROCARBON gas R290
Compressor Power.....	700 kcal/h
Pump.....	Professional carbonator pump
Inlet water Pipe.....	ø 5/16"
Dispensing area height He (in).....	12.2
Typology.....	Countertop
Supply.....	115 V - 60 Hz
Power.....	650 W - 2,6 A
	(400 W - 1,6 A Compact)
Working Room Temperature.....	Min 41°F - Max 89.6°F
NET WEIGHT lb.....	99.21
	(40 Compact)
GROSS WEIGHT lb.....	121.25
	(50 Compact)
Dimensions L x W x H (in).....	18.11 x 23.23 x 20.08
Packaging dimensions (in).....	20.87 x 26.77 x 29.53
Dispensing.....	supply option (sparkling, cold and room temperature water) with customizable portion control system
Push buttons.....	Electronic touch screen board
Energy saving device.....	Included, dedicated push buttons
Display Allarms.....	No water, No CO2, Leakage
Materials.....	All robust Stainless steel and aluminum parts
Other features.....	Safety inlet valve
	Water pressure reducer
	Co2 pressure reducer included
	Predisposition for fixing 4C Everpure filter (OPTIONAL)
	inside the machine



TOUCH SCREEN FOR GUARANTEED HYGIENE!
The smooth glass touch-screen command panel allows for rapid clearing with just a swipe of a sponge

