



Waterlogic 4 Firewall™

The Waterlogic 4 dispenser uses Firewall™ UV light to wipe out impurities.

It's in an innovative piece of technology which has been designed by us to produce the purest water. It purifies drinking water, cleansing the water to 99.9999% bacteria free, and acts as a barrier, maintaining hygiene of the dispenser. Our unique design also results in high capacity to provide hot, cold, ambient, or sparkling water, whenever you want it.

The Waterlogic Firewall guarantees a microbiologically pure, fresh and clean glass of water for every user throughout the day.

Three Steps to Greatness

Your Waterlogic dispenser has 3 core technologies which mean that what you get out of your machine is much better than what goes in:



1. Filtration: our filtration technology is really good at taking the bad stuff out and leaving the good stuff in. This stage removes chlorine and other water-borne tastes and odors.*



2. Firewall™: next the Firewall UV purification will wipe out impurities, cleansing pathogens from the water by up to 99.9999%. As an added layer of protection, the UV light keeps the dispensing nozzle from becoming contaminated.



3. BioCote®: we've got the inside covered and the outside too. As another layer of defense, BioCote keeps the dispensing area free from bacteria.



CLASS A
UV



FIREWALL
UV
SENSOR

* Where applicable



Photo: Waterlogic 4 Firewall counter top version with optional base unit for conversion to freestanding.

Performance Worthy of an Encore

Our Firewall™ technology is unique for 3 reasons:

1. Intense UV purity

The design allows for higher UV exposure which reduces bacteria, viruses and parasites that may be in the water the water, purifying up to 99.9999% of any pathogens 100% of the time.

2. Goodbye bacterial contamination

Point of dispense purification keeps the dispense nozzle free from external contamination as well as purifying the water as it fills your cup, making the freshest water possible.

3. Certified, twice

The Firewall™ technology has been tested and certified by the WQA to NSF/ANSI-55 Class A UV and NSF P231 protocol (coming soon), which is unique – no one else has these together. This means that Firewall delivers the cleanest, clearest water possible.



The Boring Bits

Water Options	Technical Features	
<ul style="list-style-type: none"> •     •    •   •   •    •  	Type available	Counter Top Freestanding
	Counter top dimensions	417mm (W) x 439mm (H) x 470mm (D) 16.4" (W) x 17.3" (H) x 18.5" (D)
	Freestanding dimensions	418mm (W) x 1238mm (H) x 470mm (D) 16.5" (W) x 48.7" (H) x 18.5" (D)
	Dispense area height	240mm (9.5")
	Weight	Counter top: 24 - 35 KG Freestanding: 42 - 53 KG
	Standard filtration supplied	1 x Carbon Block (CBC) and 1 x Granular Activated Carbon (GAC)
	Additional features	Filter timer Firewall UV sensor Drip tray overflow Thermal overload Sleep mode Leak detection
	Capacity	Hot tank: 1.2 liters (0.317 US gal.) Cold tank: 4 liters (1.18 US gal.)
	Compressor	230V (or 110v) /50Hz (60Hz) compressor
	Water temperatures	Cold 5°C/41°F Hot 87°C/189°F Extra hot 93°C/207°F
Symbols		
 Ambient water		
 Cold water		
 Sparkling water		
 Hot water		
 Extra Hot water		

Tested and Certified



Waterlogic International Limited reserves the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic, the Waterlogic logo, Firewall and the Firewall logo are registered trademarks in countries where the Group operates. Waterlogic International Limited is licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Speak to a Water Expert

USA
info@waterlogicusa.com
 + 1 402 884 7212

Rest of the world
exportsales@waterlogic.com
 + 353 1 293 1960

Waterlogic USA,
 4141 N. 156th Street,
 Omaha, NE 68116

WLI Trading Ltd.
 Suite 4, 2nd Floor Beacon Court,
 Sandyford, Dublin 18, Ireland
www.waterlogic.com

Visit Waterlogic



See Firewall
in action

