



# WL 2500

Premium features, good capacity and an excellent price make this water dispenser a popular choice for factories, canteens and offices where a number of coolers are required. The WL2500 also has safety detection systems usually found on more expensive models. UV purification is guaranteed for safe, clean, refreshing water and a carbon filtration system means the water tastes beautiful, too.

Gulp. Gulp. Gulp. Aaaaaaaaaaaaah.

### Three Steps to Greatness

Your Waterlogic dispenser has 3 core technologies which mean that what you get out of your machine is much better than what goes in:



**1. Filtration:** our filtration technology is really good at taking the bad stuff out and leaving the good stuff in. This stage removes chlorine and other water-borne tastes and odors.\*



2. In-Tank UV: next, an in-tank UV (ultra-violet) lamp purifies the water. UV light wipes out harmful bacteria such as E. Coli, Salmonella and Hepatitis to guarantee a safe, clean drink.



**3. BioCote**: we've got the inside covered and the outside too. As another layer of defense, BioCote keeps the dispensing area free of bacteria.



\*Where applicable.



### Performance Worthy of an Encore

- UV technology to eliminate bacteria
- Perfect for larger offices and factories
- Freestanding and counter-top models
- Easy connection to your existing mains water supply
- Extra hot option available to special order
- · Audible alarm warns if UV lamp has a fault
- Option for drip tray drainage



## The Boring Bits

Water Options	Technical Features		
• I I I I I I I I I I I I I I I I I I I	Type available	Freestanding Counter top	
	Freestanding dimensions	345mm (W) x 1020mm (H) x 365mm (D) 13.6in (W) x 40.2in (H) x 14.4in (D)	
	Counter top dimensions	45mm (W) x 485mm (H) x 365mm (D) 13.6in (W) x 19.1in (H) x 14.4 (D)	
	Dispense area height	215mm, 8.5in	
	Weight	Freestanding: 30KG Counter Top: 27KG	
	Standard filtration supplied (where applicable)	1x Granular Activated Carbon (GAC)	
Symbols  Ambient water	Additional features	UV sensor Leak detection Filter timer Sleep mode	
Cold water	Capacity	Hot tank: 1.5 liters (0.396 US gal.)	Cold tank: 4 liters (1.18 US gal.) freestanding, 2 liters (0.528 US gal.) counter top
Hot water  Extra Hot water	Water temperatures	Cold: 5°C/41°F Hot: 87°C/189°F Extra Hot: 93°C/203°F	
	Compressor	230V (or 110v) /50Hz (60Hz) compressor	

#### Tested and Certified







Waterlogic International Limited reserves the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo are registered trademarks in countries where the Group operates. Waterlogic International Limited is licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Llámenos para una consulta gratis

**787-708-6986** www.qualitywaterpr.com





