



Waterlogic 3 Firewall

TM

The stylish new WL3 uses Firewall™ UV purification to wipe out impurities ensuring an optimal quality of water at whatever time you dispense. The innovative Firewall technology has been designed by us to purify drinking water, typically reducing any bacterial contamination by up to 99.9999%, and also acting as a barrier, maintaining the hygiene of the dispenser. Our unique design also results in a good capacity to provide hot, cold, ambient, or sparkling water, whenever you want it.

Refreshing water starts with refreshing technology

Three Steps to Greatness

Your Waterlogic dispenser has 3 core technologies which mean that what you get out of your machine is much better than what goes in:



1. Filtration: our filtration technology is really good at taking the bad stuff out and leaving the good stuff in. This stage removes chlorine and other water-borne tastes and odors.*



2. Firewall™: next the Firewall UV purification will wipe out impurities, cleansing pathogens from the water by up to 99.9999%. As an added layer of protection, the UV light keeps the dispensing nozzle from becoming contaminated.



3. BioCote®: we've got the inside covered and the outside too. As another layer of defense, BioCote helps to keep the dispensing area free from bacteria.



* Dependant on filter type used and water conditions



Performance Worthy of an Encore

Our Firewall™ technology is unique for 3 reasons:

1. Intense UV purity

The design allows for higher UV exposure which reduces bacteria, viruses and parasites that may be in the water, purifying up to 99.9999% of any pathogens 100% of the time.

2. Goodbye bacterial contamination

Point of dispense purification keeps the dispense nozzle free from external contamination as well as purifying the water as it fills your cup, making the freshest water possible.

3. Certified, twice

The Firewall™ technology has been tested and certified by the WQA to NSF/ANSI-55 Class A UV and NSF P231 protocol, which is unique in POU water dispensers. This means that Firewall delivers the cleanest, clearest water possible.



The Boring Bits

Water Options	Technical Features			
<p>Hot option not available in counter top models</p>	Types Available	Freestanding and countertop		
	Freestanding dimensions	385mm (W) x 1140mm (H) x 365mm (D) 15.2in (W) x H 44.9in (H) x 14.4in (D)		
	Counter top dimensions	385mm (W) x 470 mm (H) x 460mm (D) 15.2in (W) x H 18.5 in (H) x 18.1 in (D)		
	Dispense area height	220mm (8.7")		
Symbols 	Weight	Freestanding: c.34 KG Counter top: c.27 KG		
	Standard filtration supplied (where applicable)	1 x 1 micron Activated Carbon Block (CBC) (inline filter connection) 1 x Polyphosphate filter (for hot options only)		
	Additional features	Firewall advanced purification UV sensor (13W UV lamp) Filter Indicator Touch sensitive control Suck-back technology on sparkling		
	Capacity	Cold: 4 litres* (freestanding) 2 litres (countertop)	Sparkling: 1.8 litres	Hot: 2 litres
	Compressor	220-240v / 50Hz or 110v / 60Hz compressor		
	Water temperatures	Cold: 5°-15°C / 41°-59°F Hot: 80°-95°C / 189°-203°F		

* With sparkling option (with dual tank), the cold tank capacity is 2 litres

Tested and Certified



Waterlogic International Limited reserves the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLT Trading Ltd (Company with licence is WLI (Trading) Limited) is licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Speak to a Water Expert

USA
info@waterlogicus.com
 + 1 402 884 7212

Waterlogic USA,
 11710 Stonegate Circle,
 Omaha, NE 68164

Rest of the world
exportsales@waterlogic.com
 + 353 1 293 1960

WLI Trading Ltd.
 Suite 4, 2nd Floor Beacon Court,
 Sandyford, Dublin 18, Ireland
www.waterlogic.com

Visit Waterlogic



See Firewall in action

