

## **BLUSODA HOT 7 FIZZ**

Cooling capacity (GAL/h) Continuos supply (GAL) Cold water temperature\*

Cooling technology

Cold Water Coil

Max hot water temperature

Hot water tank capacity

Heater wattage

Pump

Condensation

Adjustable Thermostat

Refrigerant gas

Supply

Compressor

Watts

Inlet water Pipe

Inlet CO2 Pipe

Dispensing area height He (in)

Typology

NET WEIGHT Ib

GROSS WEIGHT Ib

Dimensions L x W x H (in)

Materials

Dispensing

**Pushbuttons** 

Safety Inlet Valve (NO LEAKAGE)

Safety device to prevent accidental hot water dispensing

8

2 41 - 53.6° F

Aluminium fusion block heat exchanger Stainless Steel AISI 316

185° F

0.265 GAL

1000 W

Professional membrane carbonation pump

Ventilated

Yes

HFC R134a

115 V - 60 Hz

1/6 HP

1200W - 10A

ø 1/4" mm

ø 1/4" mm

11

Counter Top

68

73

10.28 x 19.21 x 16.46

All robust Stainless Steel

Cold water, Cold sparkling water, Hot water

Stainless steel push buttons

Included











## **OPTIONAL**

Water pressure reducer

CO<sub>2</sub> pressure reducer

Filters: UVC OUTLET (in)side the machine)

Stainless steel BLUSODA CABINET

\*rated at a room temp. of 77°F and inlet water temp. of 68°F





















